



TA-50 with high speed feeder and CT-36 conveyor shown

# TA-50

## TA-50 TABBING SYSTEM

### DESCRIPTION

The TA-50 is a heavy-duty single tabbing system that applies tabs to self-mailers at up to 20,000 pieces per hour. It has been designed for maximum productivity through ease-of-use and rugged reliability. The TA-50 quickly and easily applies a wide variety of tabs that project a professional image, tightly close your self-mailers, and allows you to take advantage of USPS® automation discounts.

The user friendly TA-50 is so simple to use that anyone in the office can operate it and complete any job, large or small, quickly and easily. Simply turn on the machine and place your media in the hopper. Designed for maximum productivity, media can be loaded while operating and the three-foot CT-36 conveyor stacker perfectly stacks hundreds of tabbed pieces.

With anchor solid construction and few moving parts, the TA-50 ensures years of trouble free operation. The TA-50 has advanced friction fed tabbing with a placement sensor ensuring proper placement of the tab on the mailpiece. The built in take-up spool keeps operation clean by reeling in the used paper backing. You can ensure a simple, effortless mailing with less downtime and higher productivity.

With a wide variety of tab colors and the choice of perforation for easier opening, you have the flexibility to project the perfect image while taking advantage of postal discounts.

Tabbing is a USPS® requirement for automation discounts for non-envelope, self-mailers. The TA-50 is the perfect compliment to the Neopost addressing line that helps your business lower postage costs, improve delivery, and always project the perfect professional image.

### APPLICATIONS

The TA-50 tabbing system is designed for easy operation within offices that may have many users and varied departmental use.

- Newsletters
- Flyers
- Double Postcards
- Catalogs
- Small Booklets

### OPTIONS

- CT-36 three-foot conveyor stacker
- HSTF high speed, high capacity feeder
- STF standard tabber feeder

### FEATURES

- Tabs up to 20,000 pieces per hour
- Applies tabs up to 1.5" in diameter
- 1/4" thickness capacity
- Little to no training required
- Large, high capacity feeder tacks
- 375, 20# bond tri-folded pieces
- Tabs pieces 5" to 12" wide, from 20 lb. thin to 1/4" thick
- Processes a wide variety of material including coated and uncoated
- Tight, secure, adjustable tab folds
- Clean, built-in waste take-up spool
- Digital, LCD reset-able piece counter
- Economical, friction-fed tabs

### SUPPLIES

- AM02-0842-00 FroTabs with perforation
- AM02-0799-12 White non-perforated
- AM02-0842-01 FroTabs without perforation
- AM02-0843-00 White with perforation
- AM02-0841-00 White removable
- AM02-0841-01 Red without perforation
- AM02-0841-02 Yellow without perforation
- AM02-0841-03 Orange without perforation
- AM02-0841-04 Dark Blue without perforation
- AM02-0841-05 Light Blue without perforation
- AM02-0841-06 Burgundy without perforation
- AM02-0841-07 Black without perforation
- AM02-0841-08 Green without perforation
- AM02-0841-09 Gold Foil without perforation
- AM02-0841-10 Silver Foil without perforation

# TA-50

## TABBING SYSTEM

### SPECIFICATIONS

#### SPEED

TA-50HS	20,000 pieces per hour
TA-50	12,000 pieces per hour

#### TAB SPOOL CAPACITY

8" friction fed spool of 5,000 one-inch  
Circular tabs

#### TAB COLORS

Perforated	Clear frosted & White
Non-Perforated	Clear frosted, White, Red, Yellow, Orange, Dark Blue, Light Blue, Burgundy, Black, Green, White removable (3-M Post-It® type glue), Gold Foil & Silver Foil

#### MEDIA THICKNESS

Min	1 sheet 20# letter fold
Max	1/4"

#### MEDIA SIZES

Height	3.5" min, 9" max
Length	5" min, 12" max

#### MEDIA

Coated, uncoated, card, 20 bond tri-fold, or recycled

#### FEEDER CAPACITY

STD standard feeder	Up to 150 pieces
HSTF high speed, high capacity feeder	Up to 350 pieces

#### PHYSICAL DIMENSIONS

##### TA-50HS

Height	17"
Depth	23"
Length	26"
Weight	95lbs.

##### TA-50

Height	17"
Depth	23"
Length	20"
Weight	69lbs.

#### POWER REQUIREMENTS

Voltage	115v
Frequency	60Hz

#### OPTIONS

CT-36 conveyor stacker  
HSTFUPG high capacity, high-speed feeder  
SL labeler and SLLINK interface kit

#### AGENCY APPROVALS

UL Listed